

# Product Number: 346-99-164-41-013000

[www.mill-max.com](http://www.mill-max.com)

## Data Sheet

---

346-99-164-41-013000 - Compliant Tail Press Fit Socket

### General Information

<sup>1</sup> <b>Product Lifecycle:</b>	Active
<b>Product Family:</b>	PCB Connector
<b>Type:</b>	Machined Pin Socket
<sup>2</sup> <b>Description:</b>	Compliant Tail Press Fit Socket
<b>Description2:</b>	Accepts .015"- .025" (0,38 - 0,635 mm) dia leads
<b>Pitch:</b>	.100" (2,540mm)
<b>Number of Pins:</b>	64
<b>Tail Type:</b>	Compliant Tail
<sup>3</sup> <b>Operating Temperature Range:</b>	-55/+125° C
<b>Country of Origin:</b>	USA
<b>ROHS:</b>	No

# 346-99-164-41-013000 - specifications

## Product Attributes

<b><sup>4</sup>Plating Code:</b>	99 - shell: 200 $\mu$ " Tin/Lead(93/7) over 100 $\mu$ " Nickel - inner contact: 100 $\mu$ " Tin/Lead(93/7) over 50 $\mu$ " Nickel
<b>Insulator Material:</b>	High Temp Thermoplastic
<b>Rows:</b>	Single Row
<b>Frame Type:</b>	N/A
<b>Contact Number:</b>	30 - Standard 4 Finger Contact

## Key Dimensions

**Accepting Lead Range:** .015"-.025" (0,381-0,635mm)  
**Insulator Height:** .110" (2,794mm)

## Electrical Specifications

<b>Contact Resistance:</b>	10.00m $\Omega$ Max
<b>Insulation Resistance:</b>	10,000 M $\Omega$ min.
<b>Rated Voltage:</b>	100 VRMS/150 VDC
<b>Dielectric Withstanding Voltage:</b>	1,000 VRMS min.

## Mounting Specifications

<b>Mounting Type:</b>	Press-Fit Into a Plated Through Hole
<b>SMT Pad Size:</b>	N/A

## Packaging Information

**<sup>5</sup>Packaging:** Packaged in Box or Tube

## Environmental & Export Classifications

<b>REACH Status:</b>	REACH Unaffected
<b>ECCN:</b>	Contact Factory
<b>HTSUS:</b>	8536.90.4040
<b>Cage Code:</b>	3N087
<b>Moisture Sensitivity Level (MSL):</b>	1 (Unlimited)
<b>Special Handling Code:</b>	UNDF
<b>Prop 65:</b>	N
<b>Static Sensitive:</b>	N

## Notes:

1. Part is Active and in Production, No Scheduled Obsolescence
2. Standard Tolerances:

Assembly tolerance: +/- .010" (.25mm)

Insulator length: +/- .005 (.13mm)

Insulator width: +/- .005 (.13mm)

Insulator height: +/- .005 (.13mm)

Pin Length: +/- .005 (.13mm)

Pin Diameter: +/- .002 (.051mm)

Pin Angle: +/- 2°

Co-planarity of SMT connectors: .005" (.13mm) up to 1" (25.4mm) in connector length

Insulator Flatness: .005" (.13mm) up to 1" (25.4mm) in connector length

3. Per IEC 60512-11-(4,-9,-10,-12)

4. **Shell Plating:** 200  $\mu$ " Tin/Lead(93/7) over 100  $\mu$ " Nickel

**Contact/Clip Plating:** 100  $\mu$ " Tin/Lead(93/7) over 50  $\mu$ " Nickel

5. Not all part numbers in the series may be packaged in tubes. Some specific part numbers may be packaged in a box.

## ADDITIONAL NOTES AND SPECIFICATIONS

In the interest of improved design, quality and performance, Mill-Max reserves the right to make changes in its specifications without prior notice. Specifications and tolerances are provided wherever possible. The tolerance on dimensions of critical to function features is typically held tighter than the stated standard tolerances, such as press-fits, holes and lengths affecting the coplanarity of SMT products. Due to the wide variety of interconnects Mill-Max offers, the specific tolerances vary from product to product. If you need information regarding the tolerance of a particular part, please contact Technical Services.

## Related Links and Documents

- Product Detail: [346-99-164-41-013000 - Compliant Tail Press Fit Socket](#)
- Environmental Compliance: <https://www.mill-max.com/rohs>