
PRODUCT NUMBER: 803-93-076-30-001000

www.mill-max.com
DATA SHEET





General Information		
1	**Product Lifecycle:**	Active
	Product Family:	PCB Connector
	Type:	Machined Pin Socket
2	**Description:**	Surface Mount Socket
	Description2:	Accepts .025"- .037" (0,635 - 0,94 mm)dia leads
	Pitch:	.100" (2,540mm)
	Number of Pins:	76
	Head Type:	N/A
	Tail Type:	Gull Wing Tail
3	**Operating Temperature Range:**	-55/+125° C
	Country of Origin:	USA
	ROHS:	No

803-93-076-30-001000 - SPECIFICATIONS

	Product Attributes	
4	**Plating Code:**	93 - shell: 200 µ" Tin/Lead(93/7) over 100 µ" Nickel - inner contact: 30 µ" Gold over 50 µ" Nickel
	Insulator Material:	High Temp Thermoplastic
	Rows:	Double Row
	Frame Type:	N/A
5	**Contact Number:**	47 - Standard 6 Finger Contact
	Mounting Tab:	N/A

	Key Dimensions	
	Accepting Lead Range:	.025"-.037" (0,635-0,940mm)
	Above Board Height:	.338" (8,585mm)
	Insulator Height:	.276" (7,010mm)
	Tail Diameter:	.024" (0,610mm)
	Tail Length:	.062" (1,575mm)

	Electrical Specifications	
6	**Current Rating:**	3 Amps
	Contact Resistance:	10.00mΩ Max
	Insulation Resistance:	10,000 MΩ min.
	Rated Voltage:	100 VRMS/150 VDC
	Dielectric Withstanding Voltage:	1,000 VRMS min.

	Mounting Specifications	
	Mounting Type:	Surface Mount
	Mounting Tab:	N/A
	SMT Pad Size:	Rectangular - 0.100" X 0.045" (2,540mm X 1,143mm)

	Packaging Information	
7	**Packaging:**	Packaged in Box or Tube
	Tape Width:	N/A

Environmental & Export Classifications	
REACH Status:	REACH Unaffected
ECCN:	Contact Factory
HTSUS:	8536.90.4040
Cage Code:	3N087
Moisture Sensitivity Level (MSL):	1 (Unlimited)
Special Handling Code:	UNDF
Prop 65:	N
Static Sensitive:	N

NOTES:

1. Part is Active and in Production, No Scheduled Obsolescence
2. **Standard Tolerances**
   Assembly tolerance: +/-.010" (.25mm)
   Connector Length "L"

Connector Length "L"	Tolerance
L ≤ 2" (L ≤ 50.8 mm)	+/- .005" (+/- .127 mm)
2< L ≤ 3" (50.8 < L ≤ 76.2 mm)	+ .007/ - .006" (+ .178/ -.152 mm)
3< L ≤ 4" (76.2 < L ≤ 101.6 mm)	+ .009 / - .007" (+ .229 / - .178 mm)
4< L ≤ 5" (101.6 < L ≤ 127 mm)	+ .011 / - .008" (+ .279 / - .203 mm)
5< L ≤ 6.4" (127 < L ≤ 162.56 mm)	+ .013 / - .009" (+ .330 / - .229 mm)

   Insulator width: +/-.005 (.13mm)
   Insulator height: +/-.005 (.13mm)
   Co-planarity of SMT connectors: .005" (.13mm) up to 1" (25.4mm) in connector length
   Insulator Flatness: .005" (.13mm) up to 1" (25.4mm) in connector length
   Pin Length: +/-.005 (.13mm)
   Pin Diameter: +/-.002 (.051mm)
   Pin Angle: +/-2°
3. Per IEC 60512-11-(4,-9,-10,-12)
4. **Shell Plating:** 200 µ" Tin/Lead(93/7) over 100 µ" Nickel
   Contact/Clip Plating: 30 µ" Gold over 50 µ" Nickel
5. Click the Link for Insertion/Extraction Force & Current/Temperature Derating Graphs
6. Per IEC 60512-5-1, Current Carrying Capacity (evaluated at 10˚ C Temp. Rise)
7. Not all part numbers in the series may be packaged in tubes. Some specific part numbers may be packaged in a box.

ADDITIONAL NOTES AND SPECIFICATIONS

In the interest of improved design, quality and performance , Mill-Max reserves the right to make changes in its specifications without prior notice. Specifications and tolerances are provided wherever possible. The tolerance on dimensions of critical to function features is typically held tighter than the stated standard tolerances, such as press-fits, holes and lengths affecting the coplanarity of SMT products. Due to the wide variety of interconnects Mill-Max offers, the specific tolerances vary from product to product. If you need information regarding the tolerance of a particular part, please contact Technical Services.

RELATED LINKS AND DOCUMENTS

- Product Detail: 803-93-076-30-001000 - Surface Mount Socket
- Engineering Notebook: **Introduction to Machined Pin PCB Connectors & Interconnects**
- Environmental Compliance: https://www.mill-max.com/rohs