




PRODUCT NUMBER: 855-22-016-10-004101

www.mill-max.com
DATA SHEET



| General Information | |
|--------------------------------|--------------------------------|
| 1 Product Lifecycle: | Active |
| Product Family: | Spring-Loaded Connector |
| Type: | Pogo Pin Header Strip |
| 2 Description: | PCB Mount Spring-Loaded Header |
| Description2: | Vertical Mount Through-Hole |
| Pitch: | .050" (1,270mm) |
| Number of Pins: | 16 |
| Head Type: | Plunger |
| Tail Type: | Solder Tail |
| 3 Operating Temperature Range: | -55/+125° C |
| Country of Origin: | USA |
| 4 ROHS: | Yes |

855-22-016-10-004101 - SPECIFICATIONS

| Product Attributes | |
|---------------------|--|
| Plating Code: | 22 - Body/Plunger Plating: 20 μ " Gold - Spring Plating: 10 μ " Gold |
| Insulator Material: | Nylon 4/6 |
| Rows: | Double Row |
| Frame Type: | N/A |
| 5 Spring Number: | 64 - Standard Force Spring Stainless Steel (Click For Graphs) |
| Plunger Type: | Round |
| Stroke: | .040" (1,016mm) |
| Mid Stroke: | 0.02 |
| Mounting Tab: | N/A |

| Key Dimensions | |
|-------------------|-----------------|
| Head Diameter: | .019" (0,483mm) |
| Initial Height: | .266" (6,756mm) |
| Insulator Height: | .075" (1,905mm) |
| Tail Diameter: | .015" (0,381mm) |
| Tail Length: | .100" (2,540mm) |

| Electrical Specifications | |
|---------------------------|---------------------|
| 6 Current Rating (Amps): | 3 Amps |
| Contact Resistance: | 20.00m Ω Max |
| Rated Voltage: | 100 VRMS/150 VDC |

| Mounting Specifications | |
|-------------------------|---------------------------|
| Mounting Type: | Through Hole Solder Mount |
| Mounting Hole: | .019" (0,483mm) |
| Mounting Tab: | N/A |
| SMT Pad Size: | N/A |

Environmental & Export Classifications

| | |
|-----------------------------------|------------------|
| Cage Code: | 3N087 |
| ECCN: | Contact Factory |
| HTSUS: | 8536.90.4040 |
| Moisture Sensitivity Level (MSL): | 1 (Unlimited) |
| Prop 65: | N |
| REACH Status: | REACH Unaffected |
| Special Handling Code: | UNDF |
| Static Sensitive: | N |

Packaging Information

| | |
|--------------|-------------------------|
| 7 Packaging: | Packaged in Box or Tube |
| Tape Width: | N/A |

NOTES:

1. Part is Active and in Production, No Scheduled Obsolescence

2. **Standard Tolerances**

Assembly tolerance: +/- .010" (.25mm)

Connector Length "L"

| Connector Length "L" | Tolerance |
|---|---------------------------------------|
| $L \leq 2"$ ($L \leq 50.8$ mm) | +/- .005" (+/- .127 mm) |
| $2 < L \leq 3"$ ($50.8 < L \leq 76.2$ mm) | + .007 / - .006" (+ .178 / - .152 mm) |
| $3 < L \leq 4"$ ($76.2 < L \leq 101.6$ mm) | + .009 / - .007" (+ .229 / - .178 mm) |
| $4 < L \leq 5"$ ($101.6 < L \leq 127$ mm) | + .011 / - .008" (+ .279 / - .203 mm) |
| $5 < L \leq 6.4"$ ($127 < L \leq 162.56$ mm) | + .013 / - .009" (+ .330 / - .229 mm) |

Insulator width: +/- .005 (.13mm)

Insulator height: +/- .005 (.13mm)

Co-planarity of SMT connectors: .005" (.13mm) up to 1" (25.4mm) in connector length

Insulator Flatness: .005" (.13mm) up to 1" (25.4mm) in connector length

Pin Length: +/- .006 (.15mm)

Pin Diameter: +/- .002 (.051mm)

Pin Angle: +/- 2°

3. Per IEC 60512-11-(4,-9,-10,-12)

4. Mill-Max products labeled with the RoHS symbol are compliant with all three ROHS Directives. All of our products previously described as RoHS (2002/95/EC) and RoHS-2 (2011/65/EC) are also compliant with RoHS-3 (2015/863/EU).


5. Current ratings are based on the pin tested in free air; the performance may be moderated when used in a connector.

6. Per IEC 60512-5-1, Current Carrying Capacity (evaluated at 10° C Temp. Rise)

7. Not all part numbers in the series may be packaged in tubes. Some specific part numbers may be packaged in a box.

ADDITIONAL PARTS, PACKAGING & ASSEMBLY INFO

Suggested P.C.B. Footprint



ADDITIONAL NOTES AND SPECIFICATIONS

In the interest of improved design, quality and performance, Mill-Max reserves the right to make changes in its specifications without prior notice. Specifications and tolerances are provided wherever possible. The tolerance on dimensions of critical to function features is typically held tighter than the stated standard tolerances, such as press-fits, holes and lengths affecting the coplanarity of SMT products. Due to the wide variety of interconnects Mill-Max offers, the specific tolerances vary from product to product. If you need information regarding the tolerance of a particular part, please contact Technical Services.

RELATED LINKS AND DOCUMENTS

- Product Detail: [855-22-016-10-004101 - PCB Mount Spring-Loaded Header](#)
- Engineering Notebook: [Introduction to Spring-Loaded Pogo Pins & Connectors](#)
- Environmental Compliance: <https://www.mill-max.com/rohs>