

Product Number: 857-10-006-10-051000

www.mill-max.com

Data Sheet

857-10-006-10-051000

General Information

¹ Product Lifecycle:	Active
Product Family:	Spring-Loaded Connector
Type:	Pad Connector with Flat Face
² Description:	PCB Mount Target Pad Header
Description2:	Vertical Mount Through Hole; Flat Face
Pitch:	.050" (1,270mm)
Number of Pins:	6
³ Operating Temperature Range:	-55/+125° C
Country of Origin:	USA
⁴ ROHS:	Yes

857-10-006-10-051000 - specifications

Product Attributes

⁵Plating Code: 10 - shell: 10 μ " Gold over 100 μ " Nickel
Insulator Material: Nylon 4/6
Rows: Double Row
Frame Type: N/A
Contact Number: N/A
Target Face Type: Flat Face

Key Dimensions

Insulator Height: .075" (1,905mm)

Electrical Specifications

Insulation Resistance: 10,000 M Ω min.
Rated Voltage: 100 VRMS/150 VDC
Dielectric Withstanding Voltage: 1,000 VRMS min.

Mechanical Specifications

⁶Shock: No Elect. Discontinuity > 1 μ s @ 50g
⁷Vibration: No Elect. Discontinuity > 1 μ s @ 10-2000HZ, 15 G

Mounting Specifications

Mounting Type: Through Hole Solder Mount

Packaging Information

⁸Packaging: Packaged in Box or Tube
Tape Width: N/A

Environmental & Export Classifications

REACH Status: REACH Unaffected
ECCN: Contact Factory
HTSUS: 8536.90.4040
Cage Code: 3N087
Moisture Sensitivity Level (MSL): 1 (Unlimited)
Special Handling Code: UNDF
Prop 65: N
Static Sensitive: N

Notes:

1. Part is Active and in Production, No Scheduled Obsolescence
2. **Standard Tolerances**

Assembly tolerance: +/- .010" (.25mm)
Connector Length "L"

Connector Length "L"	Tolerance
L \leq 2" (L \leq 50.8 mm)	+/- .005" (+/- .127 mm)

Connector Length "L"	Tolerance
2 < L ≤ 3" (50.8 < L ≤ 76.2 mm)	+ .007 / - .006" (+ .178 / - .152 mm)
3 < L ≤ 4" (76.2 < L ≤ 101.6 mm)	+ .009 / - .007" (+ .229 / - .178 mm)
4 < L ≤ 5" (101.6 < L ≤ 127 mm)	+ .011 / - .008" (+ .279 / - .203 mm)
5 < L ≤ 6.4" (127 < L ≤ 162.56 mm)	+ .013 / - .009" (+ .330 / - .229 mm)

Insulator width: +/- .005 (.13mm)
Insulator height: +/- .005 (.13mm)

Co-planarity of SMT connectors: .005" (.13mm) up to 1" (25.4mm) in connector length
Insulator Flatness: .005" (.13mm) up to 1" (25.4mm) in connector length

Pin Length: +/- .005 (.13mm)
Pin Diameter: +/- .002 (.051mm)
Pin Angle: +/- 2°

3. Per IEC 60512-11-(4,-9,-10,-12)
4. Mill-Max products labeled with the RoHS symbol are compliant with all three ROHS Directives. All of our products previously described as RoHS (2002/95/EC) and RoHS-2 (2011/65/EC) are also compliant with RoHS-3 (2015/863/EU).
5. **Pin Plating:** 10 μ" Gold over 100 μ" Nickel
6. For discrete pin only. Per IEC 60512-6-3: Test 6c: Shock
7. For discrete pin only. Per IEC 60512-6-4: Test 6d: Vibration (sinusoidal)
8. Not all part numbers in the series may be packaged in tubes. Some specific part numbers may be packaged in a box.

Additional Parts, Packaging & Assembly Info



ADDITIONAL NOTES AND SPECIFICATIONS

In the interest of improved design, quality and performance, Mill-Max reserves the right to make changes in its specifications without prior notice. Specifications and tolerances are provided wherever possible. The tolerance on dimensions of critical to function features is typically held tighter than the stated standard tolerances, such as press-fits, holes and lengths affecting the coplanarity of SMT products. Due to the wide variety of interconnects Mill-Max offers, the specific tolerances vary from product to product. If you need information regarding the tolerance of a particular part, please contact Technical Services.

Related Links and Documents

- Product Detail: [857-10-006-10-051000 - Spring-Loaded Header](#)
- Engineering Notebook: [Introduction to Spring-Loaded Pogo Pins & Connectors](#)
- Environmental Compliance: <https://www.mill-max.com/rohs>