

PIN RECEPTACLES

FOR .032" - .046" DIAMETER PINS

<p>0739 0739-0-15-XX-34-XX-10-0 Hex press-fit in .078 plated through-hole</p>	<p>8853 8853-0-15-XX-34-XX-10-0 Press-fit in .071 mounting hole</p>	<p>8838 8838-0-15-XX-34-XX-10-0 Solder mount in .086 min. mounting hole</p>	<p>3100 3100-0-15-XX-34-XX-10-0 Solder mount in .074 min. mounting hole</p>
<p>4130 4130-0-33-XX-34-XX-10-0 Wire crimp termination. Accepts wire sizes 22 AWG Max. / 26 AWG Min.</p>	<p>0720 0720-0-33-XX-34-XX-10-0 Wire crimp termination. Accepts wire sizes 20 AWG Max. / 24 AWG Min.</p>	<p>5124 5124-0-19-XX-34-XX-10-0 Wire crimp termination. Accepts wire sizes 20 AWG Max. / 24 AWG Min.</p>	<p>3735 3735-0-19-XX-34-XX-10-0 Wire crimp termination. Accepts wire sizes 18 AWG Max. / 22 AWG Min.</p>
<p>0740 0740-0-18-XX-34-XX-10-0 Press-fit in .075 mounting hole For wire sizes up to 20 AWG</p>	<p>5084 5084-0-18-XX-34-XX-10-0 Press-fit in .081 mounting hole For wire sizes up to 18 AWG</p>	<p>8731 8731-0-19-XX-34-XX-10-0 Wire crimp termination. Accepts wire sizes 22 AWG Max. / 26 AWG Min.</p>	

SPECIFICATIONS:

Shell Material: Brass Alloy 360, 1/2 Hard

Contact Material: Beryllium Copper Alloy 172, HT

Dimensions: Inches

Tolerances On: Lengths: ±.005

Diameters: ±.002

Angles: ± 2°



ORDER CODE: XXXX - X - XX - XX - 34 - XX - XX - 0

BASIC PART #

SPECIFY SHELL FINISH:

- 01 200 μ" TIN/LEAD OVER NICKEL
- ◆ 80 200 μ" TIN OVER NICKEL (RoHS)
- ◆ 15 10 μ" GOLD OVER NICKEL (RoHS)

SPECIFY CONTACT FINISH:

- 01 200 μ" TIN/LEAD OVER NICKEL
- ◆ 80 200 μ" TIN OVER NICKEL (RoHS)
- ◆ 27 30 μ" GOLD OVER NICKEL (RoHS)

SELECT CONTACT:

#34 CONTACT (DATA ON PAGE 258)

(For alternate contact choices, see group E on page 248)

