

MALE PCB PINS

PRINTED CIRCUIT PINS

<p>1959-0 1959-0-00-15-00-00-03-0 Flat face Target contact, surface mount Press-fit in .098 mounting hole</p>	<p>1959-1 1959-1-00-15-00-00-03-0 Concave face Target contact, surface mount Press-fit in .098 mounting hole</p>	<p>1969-0 1969-0-00-15-00-00-03-0 Flat face Target contact, solder Tail Press-fit in .098 mounting hole</p>	<p>1969-1 1969-1-00-15-00-00-03-0 Concave face Target contact, solder Tail Press-fit in .098 mounting hole</p>						
<p>1968-0 1968-0-01-15-00-00-03-0 Flat face Target contact, Press-fit in .097" mounting hole. For wire sizes up to 16AWG</p>	<p>1968-1 1968-1-01-15-00-00-03-0 Concave face Target contact, Press-fit in .097" mounting hole. For wire sizes up to 16AWG</p>	<p>3078 3078-X-00-15-00-00-03-0 Press-fit in .057 mounting hole For wire sizes up to 22 AWG</p> <table border="1" data-bbox="1218 924 1429 1092"> <thead> <tr> <th>Basic Part Number</th> <th>Pin Length A</th> </tr> </thead> <tbody> <tr> <td>3078-0</td> <td>.145</td> </tr> <tr> <td>3078-3</td> <td>.205</td> </tr> </tbody> </table>		Basic Part Number	Pin Length A	3078-0	.145	3078-3	.205
Basic Part Number	Pin Length A								
3078-0	.145								
3078-3	.205								
<p>3180 3180-2-01-XX-00-00-03-0 Press-fit in .055 mounting hole For wire sizes up to 22 AWG</p>	<p>0518 0518-0-01-XX-00-00-03-0 Press-fit in .059 mounting hole For wire sizes up to 22 AWG</p>	<p>4609 4609-0-07-XX-00-00-03-0 Wire crimp termination. Accepts wire sizes 18 AWG Max. / 20 AWG Min.</p>	<p>6618 6618-0-07-XX-00-00-03-0 Wire crimp termination. Accepts wire sizes 16 AWG Max. / 20 AWG Min.</p>						

SPECIFICATIONS:

Pin Material: Brass Alloy 360, 1/2 Hard
(Except where noted)

Dimensions: Inches

Tolerances On: Lengths: $\pm .005$
Diameters: $\pm .002$
Angles: $\pm 2^\circ$



ORDER CODE: XXXX - 0 - 00 - XX - 00 - 00 - 03 - 0

BASIC PART #

SPECIFY PIN FINISH:

- 01 200 μ m TIN/LEAD OVER NICKEL
- ◆ 80 200 μ m TIN OVER NICKEL (RoHS)
- ◆ 15 10 μ m GOLD OVER NICKEL (RoHS)
- ◆ 21 20 μ m GOLD OVER NICKEL (RoHS)
- ◆ 34 50 μ m GOLD OVER NICKEL (RoHS)

